


Return Air Grilles

Flush with Frame





Standard Sizes Duct Size	Free Area sq. in.	Overall Dimensions
6 x 24	65.5	$8^{3/4} \times 26^{3/4}$
8 x 24	87.3	10 ³ / ₄ x 26 ³ / ₄
6 x 30	81.9	8 ³ / ₄ x 32 ³ / ₄
8 x 30	109.2	$10^{3/4} \times 32^{3/4}$
10 x 30	136.5	$12^{3/4} \times 32^{3/4}$

Flush with Frame grilles feature a rectangular grid pattern and are the preferred style for sand and finish hardwood floors where an architecturally smooth look is desired. Each frame is grooved on the outside to accommodate most 3/4" tongue and groove flooring. All grilles are 3/4" thick, with a 1 3/8" wide frame which adds 2 3/4" to the overall dimension of the grille.

Self Rim






65.5 87.3	8 x 26 10 x 26
	8 x 32 10 x 32 12 x 32

Self Rim grilles feature a rectangular grid pattern aand can be used with most flooring surfaces; but are especially suited for prefinished flooring applications. The grille simply "drops" into a hole cut in the finished flooring. This versatile style can be used with new or existing hardwood floors, laminate, carpet, tile, or vinyl, with the rim of the grille concealing the cut edge of the finished flooring. Each grille is ³/₄" thick with a bull nosed rim that is 1" wide by ³/₈" thick.

Flush Rim






Order grilles by
duct opening

Standard Sizes Duct Size	Free Area sq. in.	Overall Dimensions
6 x 24	65.5	8 x 26
8 x 24	87.3	10 x 26
6 x 30	81.9	8 x 32
8 x 30	109.2	10 x 32
10 x 30	136.5	12 x 32

Flush Rim grilles feature a rectangular grid pattern and are the preferred style for prefinished hardwood floors where an architecturally smooth installation is required. These grilles "drop" into a pocket routed in the finished flooring. Each vent is $^{3}/_{4}$ " thick with a standard rim that is 1" wide by $^{5}/_{16}$ " thick. Custom rim thicknesses are available upon request (20% upcharge).

Flush Mount





Standard Sizes Duct Size	Free Area sq. in.	Overall Dimensions
S	Standard Sizes not a A= .455 WL	vailable

Flush Mount grilles feature a rectangular grid pattern and are used with hardwood floors as independent inserts (without frame) that rest on top of the sub floor and sit flush with the finished floor. These units are primarily used for new hardwood floor installation but may be used with existing hardwood floors. Other applications include wall or ceiling installations where a flush surface is required. Each grille is ³/₄" thick with a rail that is 1" wide with straight edges and no undercut.